

Inverted Marking Paint • Non-fluorescent

PROMARK™ — High-performance inverted marking paint, especially designed for construction site applications.

APPLICATIONS

Provides excellent adhesion to asphalt, concrete, gravel, grass, and various other surfaces. Perfect for layout work, marking, and delineating work zones.

TECHNICAL DATA

Drying time	About 5 minutes at 20°C
-------------	-------------------------

PACKAGING

CODE	COLOR	UNIT SIZE	CASE
93120	White 	420 g	12
93121	Black 	423 g	12

COVERAGE

- From 2 to 4m², depending on covering power and to the nature of the support (colour, porosity).
- 100 meters to have maximal coverage.
- Allows to realize 150 to 200 meters of marking within the speed of application and of covering wished.

REMARKS

- Do not expose to temperatures above 50°C.
- Cap denotes colour of the paint.

SAFETY RECOMMENDATIONS

- Do not expose to temperatures above 50°C.
- Keep away from sources of ignition, heat, and sunlight.
- Do not smoke.
- Do not pierce the aerosol, even after use.
- Do not burn the aerosol, even after use.
- **Refer to the SDS for more safety recommendations and information.**

PROPERTIES

- Made in Europe
- Suitable for all season use, from -20 up to + 50°C
- 12-month marking duration
- Ultra-fast drying
- Superior resistance to weather and wear
- 100% usage guarantee, no waste
- Does not contain carcinogenic, mutagenic, or toxic components for reproduction

SHELF LIFE

- 4-year shelf life from date of manufacture.
- Ideal storage between 15 to 25°C, do not freeze.

DIRECTIONS FOR USE

APPLICATION : Shake vigorously (balls must be clearly audible). Unlock the aerosol by turning left the safety cap. Use PROMARK « head down » about 4 inches from the support. After use, purge « head up » to clean out the valve and the diffuser. Lock the aerosol by turning right the safety cap.

