

## Inverted Marking Paint • Fluorescent

PROMARK™ — High-performance inverted marking paint, especially designed for construction site applications.

### APPLICATIONS

Provides excellent adhesion to asphalt, concrete, gravel, grass, and various other surfaces. Perfect for layout work, marking, and delineating work zones.

### TECHNICAL DATA

**Drying time** About 10 minutes at 20°C

### PACKAGING

CODE	COLOR	UNIT SIZE	CASE
93123	Red	347 g	12
93125	Pink	347 g	12
93126	Orange	349 g	12
93127	Yellow	347 g	12
93128	Green	347 g	12
93129	Blue	347 g	12

### COVERAGE

- From 2 to 4m<sup>2</sup>, depending on covering power and to the nature of the support (colour, porosity).
- 100 meters to have maximal coverage.
- Allows to realize 150 to 200 meters of marking within the speed of application and of covering wished.

### REMARKS

- Do not expose to temperatures above 50°C
- Cap denotes colour of the paint

### SAFETY RECOMMENDATIONS

- Do not expose to temperatures above 50°C.
- Keep away from sources of ignition, heat, and sunlight.
- Do not smoke.
- Do not pierce the aerosol, even after use.
- Do not burn the aerosol, even after use.
- **Refer to the SDS for more safety recommendations and information.**

### PROPERTIES

- Made in Europe
- Suitable for all season use, from -20 up to + 50°C
- 12-month marking duration
- Ultra-fast drying
- Very bright marking and covering capacity in a single pass
- Superior resistance to weather and wear
- 100% usage guarantee, no waste
- Does not contain carcinogenic, mutagenic, or toxic components for reproduction

### SHELF LIFE

- 4-year shelf life from date of manufacture.
- Ideal storage between 15 to 25°C, do not freeze.

### DIRECTIONS FOR USE

**APPLICATION :** Shake vigorously (balls must be clearly audible). Unlock the aerosol by turning left the safety cap. Use PROMARK «head down» about 4 inches from the support. After use, purge «head up» to clean out the valve and the diffuser. Lock the aerosol by turning right the safety cap.

